

CreatorDigital Silk

Description:

Creator 2 side coated woodfree paper with a smooth silky touch and excellent quality for digital printing.

The Creator range silk paper has multiple features to ensure optimal printing quality: high whiteness, very good ink gloss, excellent dot transfer, and high runnability.

Suitable and tested on leading digital inkjet presses. Certified for use on HP Indigo sheet-fed digital presses.

Available in a wide range of substances and formats, reels and sheets..

End uses:

Books, Brochures, Catalogues, Covers, Direct mail, Folders, Inserts, Postcards

Print methods:

Digital, HP Indigo, Inkjet

Certificates:

- [HP Indigo - Digital Silk Coated 104g](#)
- [HP Indigo - Digital Matt 125g](#)
- [HP Indigo - Digital Matt 148g](#)
- [HP Indigo - Digital Matt 150g](#)
- [HP Indigo - Digital Matt 216g](#)
- [HP Indigo - Digital Matt 220g](#)
- [HP Indigo - Digital Matt 250g](#)
- [HP Indigo - Digital Matt 251g](#)
- [HP Indigo - Digital Matt 270g](#)
- [HP Indigo - Digital Matt 275g](#)
- [HP Indigo - Digital Matt 297g](#)
- [HP Indigo - Digital Matt 300g](#)
- [HP Indigo - Digital Matt 325g](#)
- [HP Indigo - Digital Silk Coated 100g](#)
- [HP Indigo - Digital Silk Coated 110g](#)
- [HP Indigo - Digital Silk Coated 115g](#)
- [HP Indigo - Digital Silk Coated 118g](#)
- [HP Indigo - Digital Silk Coated 130g](#)
- [HP Indigo - Digital Silk Coated 135g](#)
- [HP Indigo - Digital Silk Coated 170g](#)
- [HP Indigo - Digital Silk Coated 200g](#)
- [HP Indigo - Digital Silk Coated 280g](#)
- [HP Indigo - Digital Silk Coated 350g](#)
- [HP Indigo - Digital Silk Coated 400g](#)
- [HP Indigo - Digital Silk Coated 89g](#)
- [HP Indigo - Digital Silk Coated 90g](#)
- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [ISO 50001 Energy Efficiency](#)
- [Paper Profile Creator - Motril](#)

CreatorDigital Silk

- [Paper Profile Creator - Sant Joan les Fonts](#)
- [Paper Profile GardaMatt Card](#)
- [Paper Profile GardaMatt Card Digital](#)
- [Paper Profile GardaMatt Card Duo](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

CreatorDigital Silk

Technical specifications

Property	Test Method	Unit	Tolerance	115	135	150	170	200	250	300	350
Whiteness D65/10°	ISO 11475	CIE	±3	121	121	121	121	121	121	121	121
Substance	ISO 536 TAPPI T410	g/m ²	±4%	115	135	150	170	200	250	300	350
Thickness	ISO 534 TAPPI T411	µm	±4%	100	115	131	152	181	239	299	358
Opacity	ISO 2471 TAPPI T519	%	-2.0	95.0	96.0	97.0	97.5	-	-	-	-
Brightness R457/D65	ISO 2470-2	%	±2	96.5	96.5	96.5	96.5	96.5	96.5	96.5	96.5
Parker roughness	ISO 8791-4 TAPPI T555	µm	≤1.3*std	2.4	1.8	1.8	1.8	1.8	1.8	1.8	2.1
Relative humidity	TAPPI T502	%	±7	48	48	48	48	48	48	48	48

Storage recommendations

Ideally, the paper should be stocked in pressrooms conditioned to 48% (±5) relative humidity and 23°C (±2) temperature.

In any case, extremes of temperature and humidity must be avoided.

The product properties are guaranteed for 12 months after the production date.

Values are subject to change without notice.

Last update: 07/01/2026