

CreatorMatt

Description:

Creator 2 side coated woodfree paper with an extra matt surface.

Its totally matt finish, good caliper and opacity ensure comfortable reading without unwanted reflections while maintaining color richness.

Guaranteed high whiteness and performing runnability for excellent printwork quality.

Available in a wide range of substances and formats, in sheets and reels.

End uses:

Books, Brochures, Catalogues, Covers, Direct mail, Folders, Inserts, Packaging, Postcards

Print methods:

Flexo, Laser/Dry toner, Offset, Rotogravure

Certificates:

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [ISO 50001 Energy Efficiency](#)
- [Paper Profile Creator - Motril](#)
- [Paper Profile GardaMatt Card](#)
- [Paper Profile GardaMatt Card Digital](#)
- [Paper Profile GardaMatt Card Duo](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

CreatorMatt

Technical specifications

Property	Test Method	Unit	Tolerance	90	100	115	118	125	135	150	170
Substance	ISO 536 TAPPI T410	g/m ²	±4%	90	100	115	118	125	135	150	170
Thickness	ISO 534 TAPPI T411	µm	±4%	81	91	105	102	114	115	131	152
Opacity	ISO 2471 TAPPI T519	%	-2.0	92.0	93.5	95	95	96.0	96.0	97.0	97.0
Brightness R457/D65	ISO 2470-2	%	±2	96,5	96,5	96,5	96,5	96,5	96,5	96,5	96,5
Whiteness D65/10°	ISO 11475	CIE	±3	121.3	121.3	121.3	121.3	121.3	121.3	121.3	121.3
Bekk smoothness	ISO 5627 TAPPI T479	s	±40%	-	-	-	-	220	220	200	160
Parker roughness	ISO 8791-4 TAPPI UM-555	µm	≤1.3*STD	-	-	2.4	2.4	2.4	1.8	1.8	1.8
Relative humidity	TAPPI T502	%	±7	50	50	50	50	50	50	50	50
Bendtsen roughness	-	-	-	70	80	80	-	-	-	-	-

Storage recommendations

Ideally, the paper should be stocked in pressrooms conditioned to 50% (±5) relative humidity and 23°C (±2) temperature.

In any case, extremes of temperature and humidity must be avoided.

The technical properties of the product are guaranteed for 12 months after the production date.

Values are subject to change without notice.

Last update: 04/07/2026