

## **Coral Book Ivory 1.2**

### **Description:**

High-bulk uncoated paper 1.2 bulk with high opacity and an off-white shade, aimed at the publishing sector.

Designed for offset printing, guaranteed for digital laser and pre-print laser, and recommended by major digital printing press manufacturers.

Available in a wide range of substances and formats, in sheets and reels.

### **End uses:**

Books, Brochures, Catalogues, Covers, Direct mail, Folders, Inserts, Postcards

### **Print methods:**

Digital, Flexo, Laser/Dry toner, Offset, Rotogravure

### **Certificates:**

- [PEFC Chain of Custody \(multisite\)](#)
- [FSC Chain of Custody \(multisite\)](#)
- [REACH regulation Lecta](#)
- [ISO 14001 Environment](#)
- [ISO 50001 Energy Efficiency](#)
- [ISO 9001 Quality](#)
- [ISO 45001 Health and Safety - Lecta](#)

For further details regarding compliance with food contact regulation, please contact our sales teams.

# Coral Book Ivory 1.2

## Technical specifications

Property	Test Method	Unit	Tolerance	70	80	90	100
Substance	ISO 536 TAPPI T410	g/m <sup>2</sup>	±4%	70	80	90	100
Thickness	ISO 534 TAPPI T411	µm	-	84	96	108	119
Bulk	ISO 534 TAPPI T411	cm <sup>3</sup> /g	±0.03	1.20	1.20	1.20	1.20
Opacity	ISO 2471 TAPPI T519	%	-2.0	88.0	90.0	92.0	93.0
Color a* D65/10°	ISO 5631-2	abs.	-	-0.05	-0.05	-0.05	-0.05
Color b* D65/10°	ISO 5631-2	abs.	-	12.3	12.3	12.3	12.3
Bendtsen roughness	ISO 8791-2 TAPPI T555	ml/min	±50	150	150	150	150
Cobb	ISO 535 TAPPI T441	g/m <sup>2</sup>	±5	30	30	30	35
Relative humidity	TAPPI T502	%	±7	40	40	40	40

### Storage recommendations

Paper dimensions are very sensible to humidity variations that is why we supply paper in waterproof packaging. Once the packaging is opened, a moisture exchange can take place between the paper and the environment.

Ideally, the paper should be stocked in pressrooms conditioned to 50% (±5) relative humidity and 23°C (±2) temperature. In any case, extremes of temperature and humidity must be avoided.

The technical properties of the product are guaranteed for 12 months after the production date.

Before starting a production run, check that the printability is correct on both sides of 30-50 sheets.

Values are subject to change without notice.

Last update: 04/27/2026